

Claim 8 (original) The ink jet printhead of claim 2, wherein for a set of resistors, power is routed from the resistors to the controller vias.

Claim 9 (original) The ink jet printhead of claim 1, wherein each resistor is associated with at least one power via that separates metal of the resistor from the power bus.

Claim 10 (previously amended) In an ink jet printhead, a method for increasing resistance to ink corrosion of a thin film circuit having a portion defined by at least one thin film resistor, the method comprising:

connecting a power source to the thin film resistor with a power via; and  
substantially preventing spreading of the ink corrosion from the thin film resistor to a power source with a separation barrier portion of the power via.

Claim 11 (original) The method of claim 10, wherein the power bus is separated with at least one power via.

Claim 12 (original) The method of claim 11, further comprising forming the power via within the circuit as a separation barrier between the resistors and the power bus.

Claim 13 (original) The method of claim 10, further comprising routing power from the resistors to the controller vias.

Claim 14 (original) The method of claim 10, wherein protecting the power bus from ink exposure includes terminating ink penetration at the power via.

Claim 15 (original) The method of claim 10, further comprising providing a metal stack made of a first metal layer and a second metal layer, forming an interface between the first metal layer and the second metal layer, and creating a separation barrier between the conductive portions of the thin film resistors and the power bus.

Serial No.: 10/003,938  
Attorney Docket No.: 10007153-1

Claim 16 (original) The method of claim 15, wherein the first metal layer is comprised of Aluminum Copper Silicon, the second metal layer is comprised of Aluminum and at least one of Tantalum Aluminum, Tungsten Silicon Nitride, or Tantalum Nitride which provides corrosion resistance and connects the Aluminum to the power bus.

Claim 17 (previously amended) A method of manufacturing a circuit for an ink jet printhead, the circuit having plural resistors, a power bus and a controller bus, the method comprising:

creating conductive trace routes from the power bus to power vias associated with each resistor and to each resistor and from the controller bus to controller vias associated with each resistor and to each resistor; and

creating a separation barrier within the power via to substantially prevent spreading of the ink corrosion from the resistors to the power bus and the controller bus.

Claim 18 (original) The method of claim 17, wherein providing a conductive routing scheme includes producing power vias that are defined by a conductive metal and a non-corrosive metal of the resistor.

Claim 19 (original) The method of claim 17, wherein protecting the power bus with the power vias includes separating a metal portion of the resistor from the power bus.

Claim 20 (original) The method of claim 17, wherein the circuit is a thin film circuit and includes a metal stack comprised of a first metal layer and a second metal layer, wherein the second metal layer is conformed with the vias that form an interface between the first metal layer and the second metal layer and wherein at least one via forms a separation barrier between the conductive portions of the thin film resistors and the power bus.